

RUGGED CAST IRON

Convertible Jet Pump



FEATURES

- 1-1/4" NPT suction
- Built-in thermal overload protection for safety
- Rugged cast iron pump body for durability
- Glass reinforced thermoplastic impeller
- Cast iron seal plate
- Pre-mounted, fully adjustable pressure switch
- For shallow well application up to 25' depth
- Can be used in deep well applications up to 80' depth
- Maximum pressure: 61 psi
- 1" NPT discharge and drive ports
- Pressure switch pre-set to 20/40 PSI
- Ejector kit included













RUGGED CAST IRON

Convertible Jet Pump

3/4 HORSEPOWER MOTOR





Application

Bringing potable water from a water source into the home.

Motor Specifications						
Horsepower	3/4 HP					
Voltage	115 / 230					
Amps	7.8 / 3.9					
Hertz	60 Hz					
Phase	Single					
Motor Type	Dual voltage TEFC (Totally enclosed fan cooled)					
Insulation	Class A					
Circuit Requirements	15 amp (min) individual circuit					
Duty Rating	Continuous					
Motor Shaft	Stainless Steel					
Motor Cooling	Air cooled					
Motor Protection	Auto reset thermal overload protector					

*For continuous operation, the pump hosing must be filled to prevent the motor from overheating.

Pump Specifications						
Discharge Size	1" NPT					
Drive Port Size	1" NPT					
Suction Port Size	1-1/4" NPT					
Pump Housing	Cast iron					
Impeller Material	Glass reinforced thermoplastic					
Pressure switch	20/40					
Max Pressure	61 psi					
Max Flow Rate	12.4 gpm					
Liquid Temp. Range	32°- 120° F					
Warranty	3 Years					
Weight	33.5 lbs					

Performances

Approximate gallons per minute output at 40 psi													
Lift	0'	5′	10′	15′	20′	25′	30′	40′	50′	60′	70′	80′	
Gallons Per Minute	9.8	8.6	7.9	7.1	6.4	5.8	5.1	3.8	3.1	2.3	1.4	0.7	

Dimensions

