

Washing Machine Leak Detection Kit with 90-Degree Valves

Product Specifications



Furnish and install point-of-use leak detection with audible and visual alarm, plus automatic water shut-off system designed for residential and commercial buildings. Maintenance-free, auto-cycling motorized ball valves automatically shut off the water supply whenever appliance or hoses leak.



ML20010

TECHNICAL SPECIFICATIONS

- Heavy duty full port solid brass ball valves
- Rated up to 140 PSI working pressure
- Signal Outputs: 1 Normally Open, 24VDC / 2Amp
- Easily installed in fifteen minutes
- Additional sensors may be added in series

KIT INCLUDES

- Full-Port Motorized Ball Valve(s): CNC machined. Motor operates at 6VDC.
- 1.25 X 7.5 inch, double sided water sensor
- Control Unit mounted with screws or Velcro (included).
- UL listed class 2 wall adaptor, 115AC/9VDC
- Optional Power Sources: (4) AA Batteries (not included)

APPLICABLE STANDARDS/CODES

- AB1953 & NSF 61 lead free compliant
- ICC-ES Listed(PMG-1511)
- Complies with: IPC, IRC, UPC and the National Plumbing Code of Canada(NPC) code bodies

Warranty

See warranty information for more details.

All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.



Contact your sales representative for more information or visit our website at mainlinecollection.com